



Torque Tools^{Inc.}
Pneumatic & Hydraulic Bolting Equipment
281.320.TORQ

**HYDRAULIC TORQUE
WRENCH SYSTEMS**

IBT-115 SINGLE-PORT POWER PACK

- TWO-SPEED HIGH PERFORMANCE PUMP
- EXTERNAL ADJUSTABLE PRESSURE REGULATOR
- RETRACT INTERNAL PRESSURE RELIEF VALVE FOR TOOL PROTECTION
- REMOTE CONTROL ASSEMBLY
- FOR USE WITH DOUBLE- OR SINGLE-ACTING TOOLS



IBT-MINI SINGLE-PORT POWER PACK

- TWO-SPEED GENERAL DUTY PUMP
- EXTERNAL ADJUSTABLE PRESSURE REGULATOR
- RETRACT INTERNAL PRESSURE RELIEF VALVE FOR TOOL PROTECTION
- REMOTE CONTROL ASSEMBLY
- FOR USE WITH DOUBLE- OR SINGLE-ACTING TOOLS



IBT-AIR SINGLE-PORT POWER PACK

- POWERFUL 3HP MOTOR STARTS UNDER LOAD
- EXTERNAL ADJUSTABLE PRESSURE REGULATOR
- RETRACT INTERNAL PRESSURE RELIEF VALVE FOR TOOL PROTECTION
- 25-FOOT REMOTE CONTROL ASSEMBLY
- FOR USE WITH DOUBLE- OR SINGLE-ACTING TOOLS





Torque Tools^{Inc.}
Pneumatic & Hydraulic Bolting Equipment
281.320.TORQ

SPECIFICATIONS

IBT-115 SINGLE-PORT POWER PACK

- 110 volts – 50/60 hz.*
- 20 amps
- 1-1/8 horse power
- 12000 RPM
- Maximum oil flow: 704 cubic inches per minute
- 2-gallon oil reservoir
- Overall dimensions: 17.14" x 9.5" x 18.12"
- Weight (without oil): 58 pounds

*available in 220 Volt *available in 4-port

IBT-MINI SINGLE-PORT POWER PACK

- 110 volts/60 hz.*
- 13 amps
- 1 horse power
- 4000 RPM
- Maximum oil flow: 300 cubic inches per minute
- 1.25-gallon oil reservoir
- Overall dimensions: 13.82" x 13.13" x 16.62"
- Weight (without oil): 51 pounds

*available in 220 Volt

IBT-AIR SINGLE-PORT POWER PACK

- 3 horse power
- 50 CFM @ 80 PSI
- Maximum oil flow: 465 cubic inches per minute
- 2-gallon oil reservoir
- Overall dimensions: 16.55" x 9.5" x 19.83"
- Weight (without oil): 81 pounds

*available in 4-port (As Shown)

