

RAD SMART SOCKETS™

AUDIT EQUIPMENT



Strain gauge technology measures torque with instant read-out

RAD Smart Sockets™ use RAD Torque's transducer technology combined with custom sockets to measure the actual torque applied to the bolt during a torque cycle. Its compact size and innovative technology make the Smart Socket™ a perfect audit tool for inspecting bolted joints and it can function as a calibration device for various torque tools. Patented product.

NEW
12K

NEW
18K



FEATURES

- Measures and displays peak torque
- Full data collection - export to email by PDF, XLS, CSV
- View in real time via Bluetooth onto your smartphone or tablet

CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.



IMPERIAL

SMART SOCKET™ SERIES	PART NUMBER	SOCKET HEX SIZE	DRIVE SIZE	WEIGHT (lbs.)	DIMENSION (in)	
					HEIGHT A	DIAMETER B
SMART SOCKET™ 1500/2000-M (Imperial range: 150-1500)	25448	1-1/2" (38mm)	1"	2.96	3.42"	2.83"
	22157	1-3/4"	1"	2.85	3.42"	2.83"
SMART SOCKET™ 3400/4600-M (Imperial range: 340-3400)	22110	1-7/8"	1"	4.05	3.52"	3.39"
	24124	2.0" (51mm)	1"	3.72	3.52"	3.39"
	29997	2-1/16"	1"	3.89	3.60"	3.39"
	30211	2-1/4" (57mm)	1"	3.75	3.64"	3.39"
SMART SOCKET™ 8000/10800-M (Imperial range: 800-8000)	30212	2-5/8" (67mm)	1.5"	8.04	4.50"	4.13"
	28722	2-3/4" (70mm)	1.5"	8.28	4.75"	4.13"
	21915	3.0" (76mm)	1.5"	9.76	4.75"	4.53"
SMART SOCKET™ 12000/16200-M (Imperial range: 1200-12000)	27645	3-3/4" (95mm)	1.5"	13.3	5.21"	5.30"
	32405	4-1/8" (105mm)	1.5"	16	5.20"	5.95"
	27290	4-5/8"	1.5"	17.3	5.45"	6.40"
	27289	3 7/8"	1.5"	17.1	5.45"	5.75"
SMART SOCKET 18000/24000-M* (Imperial range: 1800-18000)	33773	3 7/8"	2.5"	21	6.50"	5.71"

METRIC

SMART SOCKET™ SERIES	PART NUMBER	SOCKET HEX SIZE	DRIVE SIZE	WEIGHT (Kg)	DIMENSION (mm)	
					HEIGHT A	DIAMETER B
SMART SOCKET™ 1500/2000-M (Metric range: 200-2000)	20879	33mm	1"	1.2	100	72
	21363	36mm	1"	1.2	87	72
	22158	41mm (1-5/8")	1"	1.2	87	72
	20880	46mm (1-13/16")	1"	1.2	87	72
SMART SOCKET™ 3400/4600-M (Metric range: 460-4600)	20881	50mm	1"	1.5	89	86
	20882	55mm	1"	1.5	89	86
	20883	60mm	1"	1.5	89	86
SMART SOCKET™ 8000/10800-M (Metric range: 1100-10800)	23690	65mm (2-9/16")	1.5"	4	121	115
	28722	70mm (2-3/4")	1.5"	4	121	105
	20885	80mm	1.5"	4	121	115
SMART SOCKET™ 12000/16200-M (Metric range: 1600-16200)	25657	90mm	1.5"	5.8	126	131
	25658	100mm (3-15/16")	1.5"	7.2	132	146

Accuracy of +/-1% | *Must be used with a deep reaction arm.